

240VAC LED 1710W Lunar Lighting Tower Specs

1. Spiral cable
2. Electronic controlled hydraulic mast
3. Electronic control panel
4. Anodized **Vertical** mast – 6 sections and 8m extension
5. TIER 4 Kubota diesel engine D905-BG 5.0KW
6. Stamford alternator PI044E
7. Powder coated
8. Auto start and shut down – timer controlled
9. Two 15A, 240V power points - optional
10. 130L Diesel fuel tank
11. Battery isolator
12. Emergency shutdown
13. Silenced exhaust/muffler.
14. Noise level 65dB or LESS @7m
15. Connector to operate the light tower from mains power.
16. 110% spill containment.
17. Can operate in cold temperatures up to -40C. (Optional)
18. Glow plugs
19. Block heater (Optional)
20. Air intake valve (Optional)
21. Rubber Torsion Suspension
22. Disc Brakes

23. Fold away tow bar for transporting
24. High Temperature shutdown
25. Low oil pressure shutdown
26. High and Low voltage shutdown
27. Engine auto start and shutdown
28. All terrain tires: 225*16*70
29. SMS Communication (Optional)
30. Heavy duty Stabilizer legs x 4
31. Approximate Dimensions 185cm L x166cm W x 262cm H
32. Approximate Weight 1120kgs
33. Jump start receptacle and jumper leads
34. Dusk-dawn auto start/stop timer

* All information including technical/specifications is subject to change without notice.



LED Lunar Lighting Tower