

## 48VDC 1710W LED Lunar Lighting Tower Specs

1. Spiral cable
2. Electronic controlled hydraulic mast
3. Electronic control panel
4. Mast has 6 sections and an 8m extension
5. TIER 4 Kubota diesel engine D905-BG 5.0KW
6. Sincro FB4-48/100 with digital AVR, brushless regulation.
7. Powder coated
8. Auto start and shut down – timer controlled
9. 130L diesel fuel tank
10. Fuel consumption is 0.8L/Hr with a total run time of 162.5Hrs
11. Battery isolator
12. Emergency shutdown
13. Silenced exhaust/muffler.
14. Noise level 65dB or LESS @7m
15. 110% spill containment.
16. Can operate in cold temperatures up to -40C. (Optional)
17. Glow plugs
18. Block heater (Optional)
19. Air intake valve (Optional)
20. Rubber Torsion Suspension
21. Disc Brakes

22. Fold away tow bar for transporting
23. High Temperature shutdown
24. Low oil pressure shutdown
25. High and Low voltage shutdown
26. Engine auto start and shutdown
27. All terrain tires: 225\*16\*70
28. SMS Communication (Optional)
29. Heavy duty Stabilizer legs x 4
30. Approximate Dimensions 185cm L x166cm W x 262cm H
31. Approximate Weight 1120kgs
32. Jump start receptacle and jumper leads
33. Dusk-dawn auto start/stop timer

\* All information including technical/specifications is subject to change without notice.



**LED Lunar Lighting Tower**